


ISO-THIN PRINTABLE ACCESS CONTROL CARD



The Authenticard A-ISO family of thin printable access control cards compliment your access control system with the best proximity & contactless technology to meet your exacting requirements. A-ISO features a graphics quality surface on each side for Photo ID printing and is available with a choice of technologies to suit most access control systems.

DESIGN

- ▲ Gloss white finish
- ▲ PVC construction (standard model)
- ▲ Printable on both sides
- ▲ Standard ID-1 size compliant with ISO7810
- ▲ IP68 protection against environment
- ▲ Vertical and horizontal slot punch capability on most models
- ▲ Available with a choice of technologies





OPTIONS

- ▲ Magstripe (Hi-Co or Lo-Co)
- ▲ Multi-technology models
- ▲ Custom encoding
- ▲ Composite PVC/PET construction
- ▲ Custom artwork

TECHNOLOGIES

- ▲ 125KHz Proximity
- ▲ MIFARE
- ▲ DESFire
- ▲ Authentifire
- ▲ Legic

TECHNICAL INFORMATION



A-ISO SPECIFICATIONS		
	A-ISO LF Models	A-ISO HF Models
Operating Frequency	125 KHz	13.56 MHz
Communication	Proximity	ISO 14443A 1-4
Slot Punch Capability	Portrait and landscape marks on reverse side	None
Technology	RFID	
Net Weight	6 g	
Nominal Dimensions	85.6mm x 54mm x 0.8mm	
Power Requirement	None (Passive no-battery design)	
Operating Temperature	-25°C to 50°C	
Protection Rating	IP68	
Conformity	RoHS	
Casing Material	PVC (standard model)	
Colour	White	
Finish	Gloss (each side)	

Authenticard Readers and Tags

